

**No Chlorinated Solvents  
(No 1,1,1-Trichloroethane)**

**BATTERY TERMINAL PROTECTOR** is a long-term corrosion preventative that:

- Provides an airtight waterproof seal
- Curtails battery leakage
- Extends battery life

The coating will not crack or peel even under severe flexing. Use on battery terminals, cables, carriers or hold downs. Excellent for batteries that are used infrequently or put into storage.

**USEFUL ON:** Auto, boat, truck, forklift, golf cart and generator batteries.

**DIRECTIONS:**

Coating is most effective if surface is first prepared clean and dry. Spray an even coat over entire surface. For more severe conditions, a second coating can be applied within a few minutes. Allow several hours to set up to tack-free film. Coating may be removed with mineral spirits.



**DANGER:** Contains Liquefied Petroleum Gas (68476-86-8), Petroleum Distillates (8052-41-3) and Isoparaffinic Hydrocarbon (64741-66-8). Use only in a well-ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

For further information consult Material Safety Data Sheet.

**KEEP OUT OF REACH OF CHILDREN**



**FIRST AID: IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.  
**IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention.  
**EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.  
**IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMIS RATING:	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

**TERAND**  
INDUSTRIES, INC.

P.O. Box 667770  
Pompano Beach, FL 33066  
www.terandstore.com

**TERAND**  
The Maintenance Professional's Choice



# BATTERY TERMINAL PROTECTOR

72314

Non-Chlorinated

Flexible

Non-Tacky

Protective Coating

**DANGER:** EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)