

**Contains NO Chlorinated Solvents
NO 1,1,1-Trichloroethane
NO Hexane • NO CFC's**

Provides a super thick, black, durable, flexible, rubberized film which seals and acoustically reduces unwanted vibration and sound. Protects metal parts against the harmful effects of water, salt, sand and road chemicals. Stays pliable in winter cold, yet won't sag, melt or drip in the summer heat. Resists cracking, peeling and abrasion.

USED BY: Auto And Diesel Repair Shops, Garages, Taxi Companies, Construction Companies, Machine Shops, Equipment Manufactures, Air Conditioning Maintenance, Truck Fleet Maintenance, Aircraft and Public Transportation Maintenance Operations.

Read all instructions before using this product

**DIRECTIONS:
SHAKE WELL**

Shake vigorously until agitator ball inside rattles freely for one minute. Shake can occasionally throughout application. Apply to clean, dry surface. Do not use if temperature of can is below 60°F. Spray surface with short, even strokes from a distance of 12 to 14 inches. Several thin coats are better than one heavy coat. NOTE: After each use, invert can and apply a short burst to clear actuator.



MADE IN THE
U.S.A.

DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Toluene (108-88-3), Aliphatic Petroleum Distillate (8052-41-3), Aliphatic Petroleum Solvent (64742-89-8), Calcium Carbonate (1317-65-3) and Carbon Black (1333-86-4). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

For further
information consult
Material Safety
Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	C

**TERAND
INDUSTRIES, INC.**

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

Same
Formula
NEW LOOK!!

UNDERCOAT and SOUND DEADENER

64314

Super Thick Black Coating
Seals
Prevents Rust
Muffles Sound

DANGER: EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)