

Laboratory tested to withstand Salt Spray for 72 hours and Humidity Cabinet for 60 days. Sprays as an instant foaming, deep penetrating liquid that flows inside intricate chains and cables where the greatest stress occurs. Provides a thick foam that clings to vertical surfaces. As foam breaks, lubricant penetrates into wire rope and roller chain mechanisms. Deposits a Molybdenum Disulfide based grease and provides surfaces with superior lubricating properties. Protects against high temperature and extreme pressure environments. Grease will not break down, fly off or wash away with water or steam. Retains lubricating properties under heavy shock load, acidic environments and salt spray. Protective lubricating film prevents surface oxidation and corrosion.

FOR USE ON: Chains, Wire Cable, Open Gears, Sprockets, Chain Saws, Drag Lines, Power Drives, Fittings, Booms, Road and Construction Machinery, Hoists, Winches, Cranes, Material Handling Equipment, Tow Lines, Linkages and Roller Assemblies.

USED BY: Industrial Facilities, Shipyards, Steel Mills, Aircraft Maintenance, Material Handling, Road Equipment, Construction, Mining, Containerized Shipping Companies.

Read all instructions before using this product.

DIRECTIONS: SHAKE WELL.

Shake vigorously until agitator ball inside can rattle freely for one minute. Shake can occasionally throughout application. Spray area to be treated from a distance of 8 to 10 inches. Allow foam to penetrate and set-up to occur. For best results, repeat application periodically.



MADE IN THE U.S.A.

CAUTION: Contains Liquefied Petroleum Gas (68476-86-8), White Mineral Oil (8042-47-5) and Mineral Spirits (8052-41-3). Use only in well ventilated area. Do not expose to heat, sparks or open flame. Do not puncture or incinerate container. Avoid contact with eyes or prolonged contact with skin. Do not store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HMIS RATING:	HEALTH	1
	FLAMMABILITY	1
	REACTIVITY	0
	PERSONAL PROTECTION	B

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice



CHAIN and CABLE LUBRICANT FOAMING

86515

Foaming Action

Fortified with Moly

Deep Penetrating Action

Prevents Corrosion

High Pressure and Extreme Temperature Resistance

Residual Film Withstands Harsh Chemical Environments

CAUTION: FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.
NET WT. 15 OZ. (425 Grams)