



Same Formula
NEW LOOK!

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

DANGER: Contains Citrus Terpene (5989-27-5) and Nonylphenol Ethoxylate (127087-87-0). Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Vapor is heavier than air and may collect in low lying areas. Keep away from heat, sparks and open flame.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

IF SKIN CONTACT: Wash with plenty of soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. If continued difficulty is experienced, seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Seek medical attention immediately.

HMIS RATING: Health, 1; Flammability, 2; Reactivity, 0; Personal Protection, B.

HANDLING AND STORAGE:

Keep container closed except when in use. Do not store in unmarked containers. Store in a cool, dry place. Do not cut or weld on or near container, even when empty.

For further information, consult Material Safety Data Sheet.



**DEGREASER
and
DEODORANT
NATURAL CITRUS**

241805

Highly Dilutable
Industrial Strength
Non-Chlorinated

DANGER: FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
KEEP OUT OF REACH OF CHILDREN.
SEE OTHER CAUTIONS ON SIDE PANEL.

NET CONTENTS: 5 GALLONS



P.O. Box 667770 • Pompano Beach, FL 33066
www.terandstore.com

- Contains No Chlorinated Solvents
- Contains No Petroleum Distillates
 - Biodegradable
- Non-Caustic, Non-Acid, Non-Corrosive
 - No Harmful Vapors
 - Fresh Citrus Aroma

The safest alternative to using chlorinated solvents for degreasing and cleaning metal surfaces. A natural-based, industrial strength degreaser which quickly dissolves and removes grease, grime, asphalt, oil and tar.

USE ON:

Auto Motors, Garbage Cans and Trucks, Dumpsters, Concrete, Masonry, Road, Farm, & Construction Equipment

DIRECTIONS:

For general cleaning and degreasing, use 4 ounces to a gallon of water. Allow to set for several minutes. Wipe off or flush clean with a high pressured stream of water. For difficult remove deposits, scrub with a stiff brush before flushing clean. Repeat as necessary, Vary dilution strength according to the severity of soil and grease.

NOTE: Do not use on energized electrical equipment. Pretest on an inconspicuous area before using on plastic or painted surfaces. Do not use on freshly painted surfaces. May soften some rubbers and plastics if used excessively.