

**SHAKE WELL BEFORE USE**

Prevents condensation on cold water pipes, refrigeration lines and coils, condensers, valves and fittings. Insulates and prevents moisture build-up on water tanks, metal gutters, ice machines, air conditioning ducts and toilet tanks. Provides a "Quilting" effect by trapping moving air in special air pockets created by the stipple texture. Convenient aerosol spray is easy to apply in hard to reach areas and conforms to irregularly shaped surfaces. Dries quickly to a clean, white insulation which is nonflammable when dry. Excellent for repairing or for use in conjunction with wrap around, sleeve or foam type insulation.

**DURABLE • FLEXIBLE • WATER RESISTANT  
ADHERES TO STAINLESS STEEL, BLACK IRON, COPPER,  
BRASS, GALVANIZED AND PVC  
MAY BE PAINTED WHEN DRY**

**PREPARATION:**

Remove loose dust and dirt by wiping surface gently with a dry rag or duster. Cover surfaces under area to be treated with newspaper or a drop cloth. Protect other areas with masking tape.

**DIRECTIONS:**

**SHAKE VIGOROUSLY BEFORE AND DURING USE.** Shake can vigorously until agitator ball rattles freely. Continue shaking for at least one minute. Shake occasionally during use. For proper adhesion surface must be completely dry prior to application. Hold can 8 to 10 inches from surface to be coated. Apply with a sweeping motion using several thin coats. Allow each coat to dry for several minutes before applying next coat. If coating runs, can is too close to surface.

**IMPORTANT:** After application, clean valve by turning can upside down and applying short burst to clear actuator.



**MADE IN THE  
U.S.A.**

**DANGER:** Contains Trichloroethylene (79-01-6), Liquefied Petroleum Gas (68476-85-7), Parachlorobenzotrifluoride (98-56-6), Stearic Acid (57-11-4) and Titanium Dioxide (13463-67-7). Use only in a well ventilated area with a constant supply of fresh air. Avoid breathing vapors or spray mist. Excessive inhalation of vapors may cause nasal or respiratory irritation and central nervous system effects including dizziness, nausea and headaches. In confined or poorly ventilated areas, vapors can cause unconsciousness. If you experience eye watering, headaches or dizziness, increase air flow, wear respiratory protection or leave the area. Avoid eye contact and excessive skin contact. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

**FIRST AID: IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**KEEP OUT OF REACH  
OF CHILDREN**

<b>HMIS RATINGS:</b>	<b>HEALTH</b>	<b>2</b>
	<b>FLAMMABILITY</b>	<b>2</b>
	<b>REACTIVITY</b>	<b>1</b>
	<b>PERSONAL PROTECTION</b>	<b>B</b>

For further information consult Material Safety Data Sheet.



**TERAND  
INDUSTRIES, INC.**

P.O. Box 667770  
Pompano Beach, FL 33066  
www.terandstore.com

**TERAND**  
The Maintenance Professional's Choice



**COLD PIPE  
INSULATION**  
77015

Stops Sweating of Cold Pipes

Use On: Copper, Black Iron, Stainless Steel, Galvanized, Brass And PVC Pipe

Eliminates Drip Damage

**DANGER:** EXTREMELY FLAMMABLE. VAPOR HARMFUL. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 15 OZ. (425 Grams)