

Dry Moly Film Lubricant and Coating is a superior, long-lasting dry lubricant that adheres to almost all materials. Withstands high temperatures and pressures. Repels dust and dirt and is resistant to water, alkalies and most acids. Greatly increases operating efficiency and reduces maintenance costs. Prevents corrosion, seizing, wear, galling, binding, sticking, chattering, squeaking and scraping.

Designed for high pressure, load-bearing applications. Excellent for anti-friction and anti-seize where a dust and dirt resistant dry lubricant is desirable.

Withstands temperature ranges from -110°F to +1050°F. Resists pressures up to 100,000 psi. Contains pure Molybdenum Disulfide micro-particles which burnish themselves into metal surfaces and provide a bonded dry lubricating film.

INDUSTRIAL APPLICATIONS: Oil Drilling Equipment, Foundries, Automotive Plants, Vehicle Maintenance, Sewing Trades, Paper and Corrugated Converting, Chemical Plants, Woodworking, Marine, Agricultural & Military Equipment, Road Equipment, Aircraft Maintenance, Steel Mills and Mining Operations.

USES: May be applied wherever petroleum or synthetic lubricants are not suitable (except oxygen systems). Use on gears, bellcranks, slides, chutes, bearing surfaces, press fits, chains, conveyors, cylinder packings, shafts, valve stems, vulcanized rubber molds. High load carrying qualities assure lubrication under extreme pressures. Lubricates construction and other heavy equipment. Eliminates chattering and scraping. Resists water and dirt.

DIRECTIONS:

Shake can vigorously before application. Surface must be free from loose rust, oil, grease and old paint. Hold can 8 to 10 inches from surface and spray in a sweeping motion to insure a thin uniform coating. Allow first application 3 to 5 minutes before applying second coat.



MADE IN THE U.S.A.

DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Acetone (67-64-1), Heptane (426260-76-6), Aliphatic Hydrocarbons (8052-41-3), Toluene (108-88-3), Isopropanol (67-63-0), and Molybdenum Disulfide (1317-33-5). Use only in well ventilated area. Do not expose to heat, sparks, or open flame. Do not puncture or incinerate container. Avoid contact with eyes or prolonged contact with skin. Do not store at temperatures above 120°F. **WARNING:** This product contains chemicals known to the State of California to cause cancer, birth defects, and other reproductive harm.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMIS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice



DRY MOLY FILM LUBRICANT and COATING
95412

Non-Chlorinated

Anti-Friction

Anti-Seize

Adheres to Metal, Rubber, Glass and most Plastics

Non-Corrosive, Non-Conductive

Waterproof

Effective at Temperatures from -110°F to +1050°F

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 12 OZ. (340 Grams)