

A chemically inert, non-oily, fast-drying lubricant and release agent made with an extremely fine polytetrafluoroethylene powder. Features outstanding microscopic film forming properties and has a working temperature range of -100°F to +500°F. Leaves an odorless, stainless coating that is more slippery than silicone, graphite or oil. Excellent for reducing low speed friction. Non-conductive when dry.

DIRECTIONS:

Shake can vigorously, rattling agitator ball for a minimum of 1 full minute. Surface to be treated must be clean and dry. Hold container 5 to 10 inches from surface and spray a thin film over area.



MADE IN THE U.S.A.

DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Isoparaffinic Hydrocarbon (64741-66-8), Heptane, Branched, Cyclic, and Linear (426260-76-6), Isopropyl Alcohol (67-63-0), and Polytetrafluoroethylene (9002-84-0). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HMSIS RATING:	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

TERAND
INDUSTRIES, INC.
P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND

The Maintenance Professional's Choice



DRY LUBRICANT and RELEASE AGENT 81010

- Contains PTFE
- Chemically Inert
- Greaseless • Oil Free Coating
- Non-Staining • Fast Drying
- Heat Stable from -100°F to +500°F

DANGER: EXTREMELY FLAMMABLE.
VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.
NET WT. 10 OZ. (283 Grams)