

A powerful pinpoint spray that can be safely applied to both sides of power transmission belts even while in motion. Treatment eliminates belt slippage, increasing equipment efficiency and lengthening belt life. Will not glaze and does not attract dust or dirt.

Effective against indoor and outdoor environmental conditions.

Useful on All Types of Belts: "V" Type, Flat, Round, Made of Leather, Rubber, Fabric, and Synthetic Material

DIRECTIONS:

NOTE: In many instances protective guards must be removed in order to apply belt dressing properly. In such cases please use extreme care to prevent accidents. Be sure to replace guards after treatment.

Features a 360° valve that allows spraying with can held in upright or inverted position. Apply a little at a time to inner surface of belt while machinery is in motion. Spray using a back and forth motion until the surface is completely wet. On most belts, the spray may be applied to the sheaves, pulleys or directly onto the belt itself. Repeat occasionally to maintain full power and to optimize belt life.



MADE IN THE U.S.A.

DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Trichloroethylene (79-01-6), Polybutene (9003-29-6), and Isoparaffinic Hydrocarbon (64741-66-8). Use only in a well ventilated area with a constant supply of fresh air. Avoid breathing vapors or spray mist. Excessive inhalation of vapors may cause nasal and respiratory irritation and central nervous system effects including dizziness, nausea and headaches. In confined or poorly ventilated areas, vapors can cause unconsciousness or death. If you experience eye watering, headaches or dizziness, increase air flow, wear respiratory protection or leave the area. Avoid eye contact and excessive skin contact. Do not expose to heat or store at temperatures above 120°F. Do not puncture or incinerate container. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

HMIS RATING:	HEALTH	2
	FLAMMABILITY	2
	REACTIVITY	0
	PERSONAL PROTECTION	G

For further information consult Material Safety Data Sheet.



TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice



BELT DRESSING

79211

High Tack

Stops Slippage

Increases Equipment Efficiency

Sprays when Held Upright or Inverted

DANGER: FLAMMABLE.
VAPOR HARMFUL.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)