



**Nonfood Compounds
Program Listed H1
138579**

**(H1) FOR USE IN AND AROUND
FOOD PROCESSING AREAS**

A heat stable, non-staining, pure, dry silicone film that lubricates moving parts in food processing and packaging plants. Ideal for use on tables, conveyors, heat sealing and slicing equipment. Dry silicone formula prevents jamming and production slowdown on bottling and packaging lines. Can also be used on a non-food contact surfaces of ovens and grills to prolong time between cleanings.

USED BY: Meat and poultry plants, packaging plants, container molding operations, bottling plants.

DIRECTIONS: SHAKE WELL BEFORE USING. Spray onto clean, dry surface and allow about 60 seconds to dry. Product leaves pure silicone film which lubricates moving parts and reduces production line jamming.



**MADE IN THE
U.S.A.**

DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Isoparaffinic Hydrocarbon (64741-66-8) and Polydimethylsiloxane (63148-62-9). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult
Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



HMS RATING:	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

**TERAND
INDUSTRIES, INC.**

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice



**SILICONE
LUBRICANT
FOOD GRADE**
59011

High Viscosity

Ultra Pure

Safe on Plastic

Dries Fast

Heat Stable from -40°F to
+285°F

Non-Chlorinated

DANGER: EXTREMELY FLAMMABLE.
VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 11 OZ. (311 Grams)