

**CUTS THROUGH RUST
AT LIGHTNING BOLT SPEED**

DESCRIPTION:

- Features a forceful jet spray and a powerful penetrating catalyst which help provide rapid penetration through rust and corrosion to free frozen parts.
- Reduces friction and wear over a broad temperature range.
- Leaves a long-lasting lubricating film to defend against rust and corrosion.
- Creeps and pulls itself up, around and into cracks, crevices and threads with powerful capillary action.

DIRECTIONS:

Saturate part to be loosened and allow product to penetrate for a moment before attempting to break free. For heavily encrusted pieces a wire brush may be used to help remove corrosion. Apply a light final spray to all parts prior to reassembly.



DANGER: Contains Aromatic Hydrocarbon (64742-94-5), Mineral Oil (8042-47-5), Aliphatic Hydrocarbon (8052-41-3), 2-Butoxyethanol (111-76-2), Octamethyl- cyclotetrasiloxane (556-67-2), and Carbon Dioxide Propellant (124-38-9). Use only in a well ventilated area. Avoid contact with eyes and prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

For further information consult Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMIS RATING:	HEALTH	1
	FLAMMABILITY	2
	REACTIVITY	1
	PERSONAL PROTECTION	B

**TERAND
INDUSTRIES, INC.**

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice



**PENETRATING
CATALYST**

50615

Capillary Wet-Drilling
Action

Rapidly Cuts Through
Rust and Corrosion

Powerful Jet Spray

Long-Lasting,
Protecting Film

DANGER:

HARMFUL OR FATAL IS SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 15 OZ. (425 Grams)