

A long term, flexible, non-tacky, dust resistant coating that will not crack, peel, flake or chip over a wide temperature range (-40°F to +175°F). Adheres to most clean metal surfaces.

USE ON: Molds, offshore drilling parts, outdoor airport ground-handling equipment, castings, metal parts in ground or ocean transit, seasonal equipment in storage and any metal part needing to be temporarily sealed against corrosion.

DIRECTIONS:

Make sure surface is clean and dry. Spray a thin uniform film. Allow approximately 5 minutes to set up. For more severe storage conditions, a second coating can be applied within a few minutes. Complete setting of protective coating takes approximately two hours after spraying.



DANGER: Contains Liquefied Petroleum Gas (68476-86-8), Mineral Spirits (8052-41-3) and Isoparaffinic Hydrocarbon (64741-66-8). Use only in a well-ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

HMIS RATING	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

TERAND INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com



TERAND
The Maintenance Professional's Choice

METAL PARTS PROTECTOR

72214

Lasting Protection
Non-Tacky
Flexible Film
Non-Chlorinated
Easily Removed

DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)