

NON-FLAMMABLE • NON-CONDUCTIVE
NON-COMBUSTIBLE • NON-CORROSIVE

A residue free, super fast drying, high power spray that dissolves grease and rinses away dirt and grime without injury to working parts. Contains an acceptable replacement for 1,1,1-trichloroethane under the EPA SNAP program. Contains no CFC's, ozone depleting chemicals or petroleum distillates. Features a 36,200 volt dielectric strength combined with non-flammability make this the only degreaser safe for use on electric motors, generators, relays and control panels while equipment is in operation.

Energized equipment use only. Not to be used for motorized vehicle maintenance, or their parts.

USES: Industrial Equipment, Heating and Air Conditioning Equipment, Refrigeration Equipment, Generators, Electric Motors, Windings and Power Tools.

DIRECTIONS:

SHAKE WELL BEFORE USE. Saturate part to be cleaned. Allow to air dry. For heavily encrusted areas, brush, then rinse off with a second application. May remove some paints, pre-testing is suggested. **DO NOT USE ON PLASTICS.**



MADE IN THE
U.S.A.

WARNING: Contains Trichloroethylene (79-01-6), Isopropyl Alcohol (67-63-0) and Carbon Dioxide Propellant (124-38-9). Use only in a well ventilated area with a constant supply of fresh air. Avoid breathing vapors or spray mist. Excessive inhalation of vapors may cause nasal and respiratory irritation and central nervous system effects including dizziness, nausea and headaches. In confined or poorly ventilated areas, vapors can cause unconsciousness or fatality. If you experience eye watering, headaches or dizziness, increase air flow, wear respiratory protection or leave the area. Avoid eye contact and excessive skin contact. Do not expose to heat or store at temperatures above 120°F. Do not puncture or incinerate container. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

For further information consult Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

RECYCLING: When emptied through normal use, aerosol containers are completely recyclable. Consult local authorities.

HMS RATING:	HEALTH	2
	FLAMMABILITY	0
	REACTIVITY	1
	PERSONAL PROTECTION	G

TERAND
INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice

Same
Formula
NEW LOOK!!

**SAFETY
SOLVENT
CHLORINATED**
52118

Non-Flammable
36,000 Dielectric Strength
Non-Conductive
Non-Corrosive
Heavy Duty
Fast-Drying

WARNING: VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 18 OZ. (1 LB. 2 OZ.) (510 Grams)