

**NO Chlorinated Solvents (NO 1,1,1-Trichloroethane)
(NO Perchloroethylene) (NO Methylene Chloride)**

PENETRATES through rust and scale to loosen parts which have been frozen by corrosion.

LUBRICATES parts to ensure free and easy movement.

DEMOISTURIZES and creates a waterproof film that dries out electrical equipment, inhibits corrosion and prevents electrical discharge.

PROTECTS and creates a non-drying film that seals parts against atmospheric and mild chemical corrosion.

DIRECTIONS:

TO REMOVE CORROSION: Spray liberally directly on to dirt and scale. Allow to penetrate. Remove loosened scale, then reapply to leave an anticorrosive coating.

TO DISPLACE MOISTURE: Spray electrical equipment until thoroughly saturated. Allow to penetrate before attempting to restart, then reapply to protect surface.

TO LOOSEN FROZEN NUTS AND BOLTS: Apply liberally to frozen nuts and bolts, hinges and sliding and rotating parts. Allow to penetrate into threads. Work parts back and forth, then reapply to leave a never-dry, protective lubricating film.

**TO ENSURE ADEQUATE PROTECTION,
REAPPLY PERIODICALLY**



**MADE IN THE
U.S.A.**

CAUTION: Contains Mineral Oil (8042-47-5), Octamethylcyclotetrasiloxane (556-67-2), Decamethylcyclopentasiloxane (541-02-6), Dipropylene Glycol Monomethyl Ether (34590-94-8) and Carbon Dioxide Propellant (124-38-9). Use only in a well-ventilated area. Contents under pressure. Do not puncture or incinerate container. Avoid contact with eyes or prolonged contact with skin. Avoid contamination of food. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult
Material Safety Data Sheet.

**KEEP OUT OF REACH
OF CHILDREN**



HMS RATING:	HEALTH	1
	FLAMMABILITY	1
	REACTIVITY	0
	PERSONAL PROTECTION	B

**TERAND
INDUSTRIES, INC.**

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice



**PENETRANT
LUBRICANT
DEMOISTURANT
PROTECTANT**
20912

Non-Chlorinated

Non-Flammable

Penetrates & Cleans

Frees Frozen Fittings

Leaves Protecting, Non-Drying,
Waterproof Film

Dries Out Electrical Equipment

39,000 Volt Dielectric Strength

CAUTION: VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 12 OZ. (340 Grams)