

PENETRATING HIGH TACK FORMULA

A high tack, clear, lubricating gel which provides lubrication at temperatures from -30°F to +500°F. Penetrates as an oil to lubrication point, then forms into a tacky grease-like gel. Deposits a fine polytetrafluoroethylene and gel lubricant mixture deep inside working parts. Resists water washout and weathering. Prevents rust and corrosion while covering surfaces with a moisture proof barrier film. Safe on most plastics.

USE ON: Gears, sprockets, hinges, chains, cable, wire rope, slides, valves, pistons, rings, seals, bearings, sleeves, cams and bushings.

USED BY: Machine shops, light and heavy manufacturing, HVAC, plumbing and other trades. Automotive and virtually all maintenance or repair operations.

DIRECTIONS:

SHAKE WELL BEFORE USING. Remove cap and rotate actuator until orifice is pointed toward mark on valve cup. Spray holding can 12 to 14 inches away from surface to be treated. For hard to reach areas, insert extension tube into actuator orifice.



DANGER: Contains Liquefied Petroleum Gas (68476-85-7), Isoparaffinic Hydrocarbon (64741-66-8) and Acetone (67-64-1). Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.
EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HMIS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	1
	PERSONAL PROTECTION	B

TERAND
INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND

The Maintenance Professional's Choice

Same
Formula
NEW LOOK!!

PENETRATING GEL LUBRICANT WITH PTFE

94713

High Tack

Safe on Most Plastic

Effective From -30°F to
+500°F

DANGER: EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 13 OZ. (368 Grams)