

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: DIELECTRIC TUNE-UP GREASE 3 OZ
Item No: 22058
Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
POLYDIMETHYLSILOXANE 63148-62-9	85-95	Not Listed	Not Listed
SILICON DIOXIDE, AMORPHOUS 112945-52-5	5-15	10 mg/m ³ TWA	6 mg/m ³ TWA

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. Note: This product does not contain microcrystalline silica.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
SILICON DIOXIDE, AMORPHOUS 112945-52-5	5-15			Amorphous Silica, Group 3: Vol. 68: 1997

Medical Conditions Recognized as Being Aggravated by Exposure: None known.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): >200°F. TCC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: No special procedures.
Hazardous Products of Combustion: Carbon monoxide, Carbon dioxide, Oxides of silicon
Unusual Fire/Explosion Hazards: None.

Lower Explosive Limit: Not determined
Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store below 100 degrees F.
Handling: Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Skin: Rubber or plastic gloves.
Ventilation: Provide adequate ventilation .
Respiratory Protection: Not required under normal use. In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White, translucent grease
Odor: MILD
Boiling Point: >300°C
pH: Does not apply
Solubility in Water: Nil
Specific Gravity: 0.98
VOC Content(Wt.%): 0.4% by weight; 4.1 g/l
Vapor Pressure: <5 mmHg @ 25C
Vapor Density (Air=1): Heavier than air
Evaporation Rate: Not determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur.
Incompatibilities: Acids, Strong oxidizers
Conditions to Avoid: Heat
Hazardous Products of Combustion: Carbon monoxide, Carbon dioxide, Oxides of silicon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: None
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Product Name: DIELECTRIC TUNE-UP GREASE 3 OZ

Item No: 22058

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager

Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: 12/04/2006

Revision 4

Number: