



Nonfood Compounds
Program Listed H1
138580

(H1) FOR USE IN AND AROUND
FOOD PROCESSING AREAS

A lubricant made up of USP liquid petrolatum and propellant and providing a sanitary means of lubricating dairy and food processing equipment. Complies with FDA Regulations, CFR Title 21, paragraphs 172.878 and 178.3620.

USED ON: Slides, bearings, pistons and rings, seals and pump parts, pans, containers, belts, etc.

USED IN: Fast Service Food Preparation, Cut Meat Cold Room Packaging in Supermarkets, Prepackaged Meat Units for Franchise Outlets, Ice Cream Filling Equipment, Milk Bottle Equipment.

DIRECTIONS:

Spray 8 to 10 inches from surface to be lubricated. Leaves a pure food grade oil film. Reapply periodically.



DANGER: Contains White Mineral Oil (8042-47-5) and Liquefied Petroleum Gas (68476-85-7). Do not use near heat, sparks or open flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.
EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

KEEP OUT OF REACH OF CHILDREN



HMIS RATING:	HEALTH	0
	FLAMMABILITY	1
	REACTIVITY	0
	PERSONAL PROTECTION	A

TERAND
INDUSTRIES, INC.

P.O. Box 667770
Pompano Beach, FL 33066
www.terandstore.com

TERAND
The Maintenance Professional's Choice



**FOOD
EQUIPMENT
LUBRICANT**
94516

Non-Toxic

Odorless

Tasteless

Contains No Silicones

DANGER:

EXTREMELY FLAMMABLE.
CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 16 OZ. (1 LB.) (453 Grams)