

**FEATURES:**

Eliminates calcium build-up from moisture in air lines. Dissolves sludge, dirt and dust accumulation. Lubricates and protects all moving parts. Restores air tools to peak power and RPM's. Use regularly for preventative maintenance to cut downtime and costly repairs.

**USE FOR CLEANING & LUBRICATING:** Air Operated Tools, Sanders, Jackhammers, Drills, Saws, Impact Wrenches, Polishers, Grinders, Air Operated Motors

**DIRECTIONS:**

SHAKE WELL BEFORE USING. For interior application, insert extension tube into actuator orifice prior to use.

1. Spray into all openings including air inlet connection.
2. Allow product to penetrate for several seconds.
3. Run air tool at maximum RPM for 30 seconds.
4. Repeat above for severe conditions.
5. For long term tool storage, repeat directions 1 through 3.



MADE IN THE U.S.A.

**DANGE:** Contains Isoparaffinic Hydrocarbon (64742-66-8), Liquefied Petroleum Gas (68476-86-8), Mineral Oil (8042-47-5), and Isopropanol (67-63-0). Use only in a well-ventilated area. Contents under pressure. Do not puncture or incinerate container. Avoid contact with eyes or prolonged contact with skin. Avoid contamination of food. Do not expose to heat or store at temperatures above 120°F.

**FIRST AID: IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

For further information consult Material Safety Data Sheet.

**KEEP OUT OF REACH OF CHILDREN**



HMIS RATING:	HEALTH	1
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	B

**TERAND INDUSTRIES, INC.**

P.O. Box 667770  
Pompano Beach, FL 33066  
www.terandstore.com

**TERAND**  
The Maintenance Professional's Choice



**AIR TOOL CLEANER and LUBRICANT**  
23912

- Cleans, Lubricates, Reconditions
- Eliminates Moisture
- Prevents Rust & Corrosion
- Extends Life of Air Tools

**DANGER:** EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 12 OZ. (340 Grams)