

Contains NO Chlorinated Solvents

NO 1,1,1-Trichloroethane • NO Hexane • NO CFC's

**ROOF PATCH and LEAK SEALER** is a portable, easy to use, thick black aerosol mastic coating that seals water leaks and fills cracks and voids on most roofing surfaces. **ROOF PATCH and LEAK SEALER** is an extremely durable sealer and coating that will not sag or drip in summer heat or crack or peel in winter cold. **ROOF PATCH and LEAK SEALER** sprays as a liquid, flows into low spots, cracks and crevices then dries to a thick, black rubberized coating. Great for asphalt and fiberglass shingles, built-up tar and gravel, 1 ply rubberized and granulated roofs, mobile home and RV roofs, flashings around chimneys, vents and skylights. Helps seal concrete foundations and basements from water seepage and hydrostatic pressure. Provides an effective repair even when the surface is wet. Easy to carry, easy to apply. Eliminates mess, clean-up and burdensome pails.

Read all instructions before using this product

**DIRECTIONS:**

**SHAKE WELL.** Shake vigorously until agitator ball inside can rattles freely for one minute. Shake can occasionally throughout application. Spray surface using a sweeping motion from a distance of 12 to 14 inches. For maximum effectiveness, apply several thin coats rather than one thick layer. For best results, use only at can-temperatures above 60oF. Spray a larger area than where leak has occurred and feather edges into surrounding area with lighter applications. NOTE: After each use, invert can and apply a short burst to clear actuator. **COVERAGE:** One can treats 2 to 12 square feet depending on coating thickness.



MADE IN THE U.S.A.

**DANGER:** Contains Liquefied Petroleum Gas (68476-86-8), Toluene (108-88-3), Aliphatic Petroleum Distillate (8052-41-3), Aliphatic Petroleum Solvent (64742-89-8), Calcium Carbonate (1317-65-3) and Carbon Black (1333-86-4). Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

For further information consult Material Safety Data Sheet.



**FIRST AID: IF EYE CONTACT:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

**KEEP OUT OF REACH OF CHILDREN**

HMS RATING:	HEALTH	2
	FLAMMABILITY	3
	REACTIVITY	0
	PERSONAL PROTECTION	C

**TERAND INDUSTRIES, INC.**

P.O. Box 667770  
Pompano Beach, FL 33066  
www.terandstore.com

**TERAND**  
The Maintenance Professional's Choice



# ROOF PATCH and LEAK SEALER

64714

**QUICKLY SEALS LEAKS ON:**

Flat Roofs, Chimney and Sky Light Flashings, Drip Edges, Mobile Home and Camper Roofs, Gravel Stops, One Ply Rubberized Systems, Metal Buildings, Below Grade Foundations, Off Ridge Vents, Fiberglass Shingle Roofs, Overlapped Seams, Gutters and Downspouts, Vent Pipe Flashings, Asphalt Shingle Roofs, Seams with Pinholes

**EFFECTIVE ON:**

Asphalt, Composition, Tile, Slate, Felt, Wood and Metal Roofing Materials

Can Be Used on Wet Surfaces

Unaffected by Weather

Seals Out the Elements

**DANGER:** EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON BACK PANEL.

NET WT. 14 OZ. (396 Grams)